

Beams and Columns – Dimensions Available Upon Request

Beams and Columns – Dimensions Available Upon Request

Name and Column		Dimensions Available Upon Request										
						Width (mm)						
64	111	162	267	321	371	422	476	527	578	632	657	683
Depths (mm)												
140	111											
191	191	162										
241	241	241										
292	292	292	267									
343	343	343	343	321								
394	394	394	394	394	371							
445	445	445	445	445	445	422						
495	495	495	495	495	495	495	476					
546	546	546	546	546	546	546	546	527				
597	597	597	597	597	597	597	597	597	578			
648	648	648	648	648	648	648	648	648	648	632		
699	699	699	699	699	699	699	699	699	699	699	657	683
749	749	749	749	749	749	749	749	749	749	749	749	749
	803	803	803	803	803	803	803	803	803	803	803	803
	854	854	854	854	854	854	854	854	854	854	854	854
	905	905	905	905	905	905	905	905	905	905	905	905
	956	956	956	956	956	956	956	956	956	956	956	956
	1 006	1 006	1 006	1 006	1 006	1 006	1 006	1 006	1 006	1 006	1 006	1 006
	1 057	1 057	1 057	1 057	1 057	1 057	1 057	1 057	1 057	1 057	1 057	1 057
	1 108	1 108	1 108	1 108	1 108	1 108	1 108	1 108	1 108	1 108	1 108	1 108
	1 159	1 159	1 159	1 159	1 159	1 159	1 159	1 159	1 159	1 159	1 159	1 159
	1 210	1 210	1 210	1 210	1 210	1 210	1 210	1 210	1 210	1 210	1 210	1 210
	1 260	1 260	1 260	1 260	1 260	1 260	1 260	1 260	1 260	1 260	1 260	1 260
	1 311	1 311	1 311	1 311	1 311	1 311	1 311	1 311	1 311	1 311	1 311	1 311
		1 362	1 362	1 362	1 362	1 362	1 362	1 362	1 362	1 362	1 362	1 362
		1 413	1 413	1 413	1 413	1 413	1 413	1 413	1 413	1 413	1 413	1 413
		1 464	1 464	1 464	1 464	1 464	1 464	1 464	1 464	1 464	1 464	1 464
		1 514	1 514	1 514	1 514	1 514	1 514	1 514	1 514	1 514	1 514	1 514
		1 565	1 565	1 565	1 565	1 565	1 565	1 565	1 565	1 565	1 565	1 565
		1 619	1 619	1 619	1 619	1 619	1 619	1 619	1 619	1 619	1 619	1 619
		1 670	1 670	1 670	1 670	1 670	1 670	1 670	1 670	1 670	1 670	1 670
		1 721	1 721	1 721	1 721	1 721	1 721	1 721	1 721	1 721	1 721	1 721
		1 772	1 772	1 772	1 772	1 772	1 772	1 772	1 772	1 772	1 772	1 772
		1 822	1 822	1 822	1 822	1 822	1 822	1 822	1 822	1 822	1 822	1 822
		1 873	1 873	1 873	1 873	1 873	1 873	1 873	1 873	1 873	1 873	1 873
		1 924	1 924	1 924	1 924	1 924	1 924	1 924	1 924	1 924	1 924	1 924
			1 975	1 975	1 975	1 975	1 975	1 975	1 975	1 975	1 975	1 975
			2 026	2 026	2 026	2 026	2 026	2 026	2 026	2 026	2 026	2 026
			2 076	2 076	2 076	2 076	2 076	2 076	2 076	2 076	2 076	2 076
			2 127	2 127	2 127	2 127	2 127	2 127	2 127	2 127	2 127	2 127
			2 178	2 178	2 178	2 178	2 178	2 178	2 178	2 178	2 178	2 178
			2 229	2 229	2 229	2 229	2 229	2 229	2 229	2 229	2 229	2 229
			2 280	2 280	2 280	2 280	2 280	2 280	2 280	2 280	2 280	2 280
			2 330	2 330	2 330	2 330	2 330	2 330	2 330	2 330	2 330	2 330
			2 384	2 384	2 384	2 384	2 384	2 384	2 384	2 384	2 384	2 384
			2 435	2 435	2 435	2 435	2 435	2 435	2 435	2 435	2 435	2 435

Notes:

- Any use of these dimensions shall be authorized by the plant on a case-by-case basis.
- Members of dimensions in black are cold pressed for lengths up to 18.9 m (optimum dimensions for straight members) and hot pressed for lengths between 18.9 and 24.4 m (maximum length).
- Members of dimensions in grey are cold pressed (maximum length of 24.4 m).
- Members of shaded dimensions are cold pressed using manual techniques (maximum length of 24.4 m).
- Depth-to-width ratio shall be limited to 12:1.
- Other dimensions are available upon request; please contact Nordic.