

Beams and Columns – Dimensions Available Upon Request

Beams and Columns – Dimensions Available Upon Request

						Width (in.)								
2-1/2	4-3/8	6-3/8	10-1/2	12-5/8	14-5/8	16-5/8	18-3/4	20-3/4	22-3/4	24-7/8	25-7/8	26-7/8		
Depths (in.)														
5-1/2	4-3/8													
7-1/2	7-1/2	6-3/8												
9-1/2	9-1/2	9-1/2												
11-1/2	11-1/2	11-1/2	10-1/2											
13-1/2	13-1/2	13-1/2	13-1/2	12-5/8										
15-1/2	15-1/2	15-1/2	15-1/2	15-1/2	14-5/8									
17-1/2	17-1/2	17-1/2	17-1/2	17-1/2	17-1/2	16-5/8								
19-1/2	19-1/2	19-1/2	19-1/2	19-1/2	19-1/2	19-1/2	18-3/4							
21-1/2	21-1/2	21-1/2	21-1/2	21-1/2	21-1/2	21-1/2	21-1/2	20-3/4						
23-1/2	23-1/2	23-1/2	23-1/2	23-1/2	23-1/2	23-1/2	23-1/2	23-1/2	22-3/4					
25-1/2	25-1/2	25-1/2	25-1/2	25-1/2	25-1/2	25-1/2	25-1/2	25-1/2	25-1/2	24-7/8				
27-1/2	27-1/2	27-1/2	27-1/2	27-1/2	27-1/2	27-1/2	27-1/2	27-1/2	27-1/2	27-1/2	25-7/8	26-7/8		
29-1/2	29-1/2	29-1/2	29-1/2	29-1/2	29-1/2	29-1/2	29-1/2	29-1/2	29-1/2	29-1/2	29-1/2	29-1/2		
	31-5/8	31-5/8	31-5/8	31-5/8	31-5/8	31-5/8	31-5/8	31-5/8	31-5/8	31-5/8	31-5/8	31-5/8		
	33-5/8	33-5/8	33-5/8	33-5/8	33-5/8	33-5/8	33-5/8	33-5/8	33-5/8	33-5/8	33-5/8	33-5/8		
	35-5/8	35-5/8	35-5/8	35-5/8	35-5/8	35-5/8	35-5/8	35-5/8	35-5/8	35-5/8	35-5/8	35-5/8		
	37-5/8	37-5/8	37-5/8	37-5/8	37-5/8	37-5/8	37-5/8	37-5/8	37-5/8	37-5/8	37-5/8	37-5/8		
	39-5/8	39-5/8	39-5/8	39-5/8	39-5/8	39-5/8	39-5/8	39-5/8	39-5/8	39-5/8	39-5/8	39-5/8		
	41-5/8	41-5/8	41-5/8	41-5/8	41-5/8	41-5/8	41-5/8	41-5/8	41-5/8	41-5/8	41-5/8	41-5/8		
	43-5/8	43-5/8	43-5/8	43-5/8	43-5/8	43-5/8	43-5/8	43-5/8	43-5/8	43-5/8	43-5/8	43-5/8		
	45-5/8	45-5/8	45-5/8	45-5/8	45-5/8	45-5/8	45-5/8	45-5/8	45-5/8	45-5/8	45-5/8	45-5/8		
	47-5/8	47-5/8	47-5/8	47-5/8	47-5/8	47-5/8	47-5/8	47-5/8	47-5/8	47-5/8	47-5/8	47-5/8		
	49-5/8	49-5/8	49-5/8	49-5/8	49-5/8	49-5/8	49-5/8	49-5/8	49-5/8	49-5/8	49-5/8	49-5/8		
	51-5/8	51-5/8	51-5/8	51-5/8	51-5/8	51-5/8	51-5/8	51-5/8	51-5/8	51-5/8	51-5/8	51-5/8		
		53-5/8	53-5/8	53-5/8	53-5/8	53-5/8	53-5/8	53-5/8	53-5/8	53-5/8	53-5/8	53-5/8		
		55-5/8	55-5/8	55-5/8	55-5/8	55-5/8	55-5/8	55-5/8	55-5/8	55-5/8	55-5/8	55-5/8		
		57-5/8	57-5/8	57-5/8	57-5/8	57-5/8	57-5/8	57-5/8	57-5/8	57-5/8	57-5/8	57-5/8		
		59-5/8	59-5/8	59-5/8	59-5/8	59-5/8	59-5/8	59-5/8	59-5/8	59-5/8	59-5/8	59-5/8		
		61-5/8	61-5/8	61-5/8	61-5/8	61-5/8	61-5/8	61-5/8	61-5/8	61-5/8	61-5/8	61-5/8		
		63-3/4	63-3/4	63-3/4	63-3/4	63-3/4	63-3/4	63-3/4	63-3/4	63-3/4	63-3/4	63-3/4		
		65-3/4	65-3/4	65-3/4	65-3/4	65-3/4	65-3/4	65-3/4	65-3/4	65-3/4	65-3/4	65-3/4		
		67-3/4	67-3/4	67-3/4	67-3/4	67-3/4	67-3/4	67-3/4	67-3/4	67-3/4	67-3/4	67-3/4		
		69-3/4	69-3/4	69-3/4	69-3/4	69-3/4	69-3/4	69-3/4	69-3/4	69-3/4	69-3/4	69-3/4		
		71-3/4	71-3/4	71-3/4	71-3/4	71-3/4	71-3/4	71-3/4	71-3/4	71-3/4	71-3/4	71-3/4		
		73-3/4	73-3/4	73-3/4	73-3/4	73-3/4	73-3/4	73-3/4	73-3/4	73-3/4	73-3/4	73-3/4		
		75-3/4	75-3/4	75-3/4	75-3/4	75-3/4	75-3/4	75-3/4	75-3/4	75-3/4	75-3/4	75-3/4		
		77-3/4	77-3/4	77-3/4	77-3/4	77-3/4	77-3/4	77-3/4	77-3/4	77-3/4	77-3/4	77-3/4		
		79-3/4	79-3/4	79-3/4	79-3/4	79-3/4	79-3/4	79-3/4	79-3/4	79-3/4	79-3/4	79-3/4		
		81-3/4	81-3/4	81-3/4	81-3/4	81-3/4	81-3/4	81-3/4	81-3/4	81-3/4	81-3/4	81-3/4		
		83-3/4	83-3/4	83-3/4	83-3/4	83-3/4	83-3/4	83-3/4	83-3/4	83-3/4	83-3/4	83-3/4		
		85-3/4	85-3/4	85-3/4	85-3/4	85-3/4	85-3/4	85-3/4	85-3/4	85-3/4	85-3/4	85-3/4		
		87-3/4	87-3/4	87-3/4	87-3/4	87-3/4	87-3/4	87-3/4	87-3/4	87-3/4	87-3/4	87-3/4		
		89-3/4	89-3/4	89-3/4	89-3/4	89-3/4	89-3/4	89-3/4	89-3/4	89-3/4	89-3/4	89-3/4		
		91-3/4	91-3/4	91-3/4	91-3/4	91-3/4	91-3/4	91-3/4	91-3/4	91-3/4	91-3/4	91-3/4		
		93-7/8	93-7/8	93-7/8	93-7/8	93-7/8	93-7/8	93-7/8	93-7/8	93-7/8	93-7/8	93-7/8		
		95-7/8	95-7/8	95-7/8	95-7/8	95-7/8	95-7/8	95-7/8	95-7/8	95-7/8	95-7/8	95-7/8		

Notes:

- Any use of these dimensions shall be authorized by the plant on a case-by-case basis.
- Members of dimensions in black are cold pressed for lengths up to 62 ft (optimum dimensions for straight members) and hot pressed for lengths between 62 and 80 ft (maximum length).
- Members of dimensions in grey are cold pressed (maximum length of 80 ft).
- Members of shaded dimensions are cold pressed using manual techniques (maximum length of 80 ft).
- Depth-to-width ratio shall be limited to 12:1.
- Other dimensions are available upon request; please contact Nordic.