

 BOSTIK		Page: 1
SAFETY DATA SHEET		Revision Date: 07/12/2022
		Print Date: 12/5/2023
		SDS Number: 000000156392
Isoet™ WD3-A322UV ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 719785		Version: 2.1

SECTION 1. IDENTIFICATION

Product identifier

Trade name : Isoet™ WD3-A322UV
 ADHESIVE
 ™ Trademark, Bostik or its subsidiaries, registered in various countries

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : ADHESIVE

Details of the supplier of the safety data sheet Bostik Canada Ltd./Bostik Canada Ltee 655 Boul Alphonse-Deshales Becancour, Quebec, G9H 2Y8 Canada Tel: +1 (514) 593-0418 EHSproductsafety.US@bostik.com	Emergency telephone number Chemtrec 1-800-424-9300, outside US 1-703-527-3887 Regulatory information Rocky Mountain Poison center: 1-866-767-5089
--	--

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Carcinogenicity : Category 1A

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H350 May cause cancer.
 H361 Suspected of damaging fertility or the unborn child.

Precautionary statements : **Prevention:**

 BOSTIK		Page: 2
SAFETY DATA SHEET		Revision Date: 07/12/2022
		Print Date: 12/5/2023
		SDS Number: 000000156392
Isoset™ WD3-A322UV ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 719785		Version: 2.1

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
Storage:
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
LIMESTONE Limestone	1317-65-3	Not a hazardous substance or mixture.	22.35
toluene Benzene, methyl-	108-88-3	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361 STOT SE 3; H336 STOT RE 2; H373 Asp. Tox. 1; H304 PHNOC 1;	0.80
PENTA-NA DIETHYLENETRIAMINE PENTAACETATE	140-01-2	Comb Dust 1; Acute Tox. 4; H332	0.604



BOSTIK

SAFETY DATA SHEET

Revision Date: 07/12/2022

Print Date: 12/5/2023

SDS Number: 000000156392

Version: 2.1

IsoSet™ WD3-A322UV ADHESIVE
™ Trademark, Bostik or its subsidiaries, registered in various countries
719785

Glycine, N,N-bis[2-[bis(carboxymethyl)amino]ethyl]-, pentasodium salt		Eye Irrit. 2A; H319 Repr. 2; H361	
CRISTOBALITE Cristobalite (SiO ₂)	14464-46-1	Carc. 1A; H350 STOT RE 1; H372	0.2235
PHOSPHORIC ACID, TRIBUTYL ESTER Phosphoric acid tributyl ester	126-73-8	Acute Tox. 4; H302 Skin Irrit. 2; H315 Carc. 2; H351	0.20

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Call a POISON CENTRE or doctor/physician if exposed or you feel unwell. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. If eye irritation persists, consult a specialist.
If swallowed	: Obtain medical attention. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and	: Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

 BOSTIK		Page: 4
SAFETY DATA SHEET		Revision Date: 07/12/2022
		Print Date: 12/5/2023
		SDS Number: 000000156392
Isoset™ WD3-A322UV ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 719785		Version: 2.1

delayed

the skin may include:
 stomach or intestinal upset (nausea, vomiting, diarrhea)
 irritation (nose, throat, airways)
 May cause cancer.
 Suspected of damaging fertility or the unborn child.

Notes to physician

: No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Carbon dioxide (CO₂)
 Dry chemical

Unsuitable extinguishing media : High volume water jet

Hazardous combustion products : Carbon dioxide (CO₂)
 Carbon monoxide
 Burning produces irritant fumes.

Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
 Ensure adequate ventilation.
 Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.

 BOSTIK		Page: 5
SAFETY DATA SHEET		Revision Date: 07/12/2022
		Print Date: 12/5/2023
		SDS Number: 000000156392
Isoset™ WD3-A322UV ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 719785		Version: 2.1

If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
LIMESTONE	1317-65-3	TWA	10 mg/m ³	CA AB OEL
		TWA EV	10 mg/m ³ total dust	CA QC OEL
		TWA	10 mg/m ³ Total dust	CA BC OEL



BOSTIK

SAFETY DATA SHEET

Revision Date: 07/12/2022

Print Date: 12/5/2023

SDS Number: 000000156392

Version: 2.1

Isoet™ WD3-A322UV ADHESIVE
™ Trademark, Bostik or its subsidiaries, registered in various countries
719785

		TWA	3 mg/m3 respirable dust fraction	CA BC OEL
		STEL	20 mg/m3	CA BC OEL
toluene	108-88-3	TWA	50 ppm 188 mg/m3	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	50 ppm 188 mg/m3	CA QC OEL
CRISTOBALITE	14464-46-1	TWA	0.025 mg/m3 Respirable particulates	CA AB OEL
		TWA	0.05 mg/m3 Respirable fraction	CA ON OEL
		TWAEV	0.05 mg/m3 respirable dust	CA QC OEL
		TWA	0.025 mg/m3 Respirable (Silica)	CA BC OEL
PHOSPHORIC ACID, TRIBUTYL ESTER	126-73-8	TWA	0.2 ppm 2.2 mg/m3	CA AB OEL
		TWA	0.2 ppm	CA BC OEL
		TWAEV	5 mg/m3 inhalable fraction and vapour	CA QC OEL

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter within the capabilities of the respirator/filter combination.
Where concentrations are above recommended limits or are unknown, or a cartridge type respirator is not adequate, wear a positive-pressure supplied-air respirator.

Hand protection

Material : butyl-rubber
Break through time : 480 min
Glove thickness : > 0.5 mm

Remarks : The exact break through time can be obtained from the protective glove producer and this has to be observed. Gloves should be discarded and replaced if there is any indication of

 BOSTIK		Page: 7
SAFETY DATA SHEET		Revision Date: 07/12/2022
		Print Date: 12/5/2023
		SDS Number: 000000156392
Isoset™ WD3-A322UV ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 719785		Version: 2.1

degradation or chemical breakthrough.

- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Wear as appropriate:
 Impervious clothing
 Safety shoes
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.
 Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : Wash hands before breaks and at the end of workday.
 When using do not eat or drink.
 When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Physical state : liquid
- Colour : No data available
- Odour : aromatic
- Odour Threshold : No data available
- pH : 6.3
- Melting point/freezing point : not determined
- Boiling point/boiling range : 212 °F / 100 °C
 (1,013.333333 hPa)
 Calculated Phase Transition Liquid/Gas
- Flash point : 100 °C Calculated Flash Point
- Evaporation rate : > 1
 Ethyl Ether = 1
- Upper explosion limit : Upper explosion limit
 not determined
- Lower explosion limit : Lower explosion limit

 BOSTIK		Page: 8
SAFETY DATA SHEET		Revision Date: 07/12/2022
		Print Date: 12/5/2023
		SDS Number: 000000156392
Isoet™ WD3-A322UV ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 719785		Version: 2.1

Vapour pressure	: not determined 31.733333 hPa (20 °C) Calculated Vapor Pressure
Relative vapour density	: > 1(Air = 1.0)
Relative density	: 1.15 - 1.25 (25 °C)
Density	: 1.15 - 1.25 g/cm3 (25 °C)
Solubility(ies)	
Water solubility	: not determined
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: not determined
Viscosity, kinematic	: not determined
Oxidizing properties	: Not applicable
Molecular weight	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: excessive heat Freezing temperatures.
Incompatible materials	: Acids ammonium salts aluminum salts

 BOSTIK		Page: 9
SAFETY DATA SHEET		Revision Date: 07/12/2022
		Print Date: 12/5/2023
		SDS Number: 000000156392
Isoet™ WD3-A322UV ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 719785		Version: 2.1

Fluorine
 reactive metals such as aluminum and magnesium
 Strong oxidizing agents

Hazardous decomposition
 products

calcium oxide
 Hydrocarbons
 Acetone
 Carbon monoxide
 Carbon dioxide (CO₂)

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
 Skin contact
 Eye Contact
 Ingestion

Acute toxicity

Not classified based on available information.

Components:

LIMESTONE:

Acute oral toxicity : LD₅₀ (Rat): 6,450 mg/kg

toluene:

Acute oral toxicity : LD₅₀ (Rat, male): 5,580 mg/kg

Acute inhalation toxicity : LC₅₀ (Rat): 28.1 mg/l
 Exposure time: 4 h
 Test atmosphere: vapour
 Method: OECD Test Guideline 403

Acute dermal toxicity : LD₅₀ (Rabbit): 12,267 mg/kg

PENTA-NA DIETHYLENETRIAMINE PENTAACETATE:

Acute oral toxicity : LD₅₀ (Rat): 4,550 mg/kg

Acute inhalation toxicity : Assessment: The component/mixture is classified as acute inhalation toxicity, category 4.

PHOSPHORIC ACID, TRIBUTYL ESTER:

Acute oral toxicity : LD₅₀ (Rat): 1,550 mg/kg

 BOSTIK		Page: 10
SAFETY DATA SHEET		Revision Date: 07/12/2022
		Print Date: 12/5/2023
		SDS Number: 000000156392
Isoset™ WD3-A322UV ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 719785		Version: 2.1

Acute dermal toxicity : LD50 (Rabbit): > 3,100 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

LIMESTONE:

Result: Slight, transient irritation

toluene:

Species: Rabbit

Method: Regulation (EC) No. 440/2008, Annex, B.4

Result: Irritating to skin.

PENTA-NA DIETHYLENETRIAMINE PENTAACETATE:

Result: No skin irritation

CRISTOBALITE:

Result: Slight, transient irritation

PHOSPHORIC ACID, TRIBUTYL ESTER:

Result: Irritating to skin.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

LIMESTONE:

Result: Slight, transient irritation

toluene:

Result: Slight, transient irritation

PENTA-NA DIETHYLENETRIAMINE PENTAACETATE:

Result: Irritating to eyes.

CRISTOBALITE:

Result: Slight, transient irritation

 BOSTIK		Page: 11
SAFETY DATA SHEET		Revision Date: 07/12/2022
		Print Date: 12/5/2023
		SDS Number: 000000156392
Isoset™ WD3-A322UV ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 719785		Version: 2.1

PHOSPHORIC ACID, TRIBUTYL ESTER:
 Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

toluene:

Test Type: Maximisation Test

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.

Result: Did not cause sensitisation on laboratory animals.

PHOSPHORIC ACID, TRIBUTYL ESTER:

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Components:

toluene:

Genotoxicity in vitro

: Test Type: In vitro gene mutation study in bacteria

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: Regulation (EC) No. 440/2008, Annex, B.13/14

(Ames test)

Result: negative

: Test Type: In vitro mammalian cell gene mutation test

Test species: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo

: Test Type: chromosome aberration assay

Test species: Rat

Cell type: Bone marrow

Result: negative

PENTA-NA DIETHYLENETRIAMINE PENTAACETATE:

Genotoxicity in vitro

: Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

 BOSTIK		Page: 12
SAFETY DATA SHEET		Revision Date: 07/12/2022
		Print Date: 12/5/2023
		SDS Number: 000000156392
Isoset™ WD3-A322UV ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 719785		Version: 2.1

Carcinogenicity

May cause cancer.

Components:

CRISTOBALITE:

Carcinogenicity - : Human carcinogen.
Assessment

PHOSPHORIC ACID, TRIBUTYL ESTER:

Carcinogenicity - : Limited evidence of carcinogenicity in animal studies
Assessment

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

toluene:

Reproductive toxicity - : Some evidence of adverse effects on development, based on
Assessment animal experiments.

PENTA-NA DIETHYLENETRIAMINE PENTAACETATE:

Reproductive toxicity - : Some evidence of adverse effects on sexual function and
Assessment fertility, and/or on development, based on animal experiments.

STOT - single exposure

Not classified based on available information.

Components:

toluene:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Components:

toluene:

Exposure routes: Inhalation

Target Organs: Central nervous system, Peripheral nervous system

Assessment: May cause damage to organs through prolonged or repeated exposure.

CRISTOBALITE:

Exposure routes: inhalation (dust/mist/fume)

Target Organs: Respiratory system, Kidney

Assessment: Causes damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

 BOSTIK		Page: 13
SAFETY DATA SHEET		Revision Date: 07/12/2022
		Print Date: 12/5/2023
		SDS Number: 000000156392
Isoet™ WD3-A322UV ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 719785		Version: 2.1

Components:

toluene:

Species: Rat, male and female

NOAEL: 625 mg/kg

Application Route: Oral

Exposure time: 13 wks

Method: Regulation (EC) No. 440/2008, Annex, B.26

Species: Rat, male and female

NOAEL: 1.131 mg/l

Application Route: inhalation (vapour)

Method: OECD Test Guideline 453

Aspiration toxicity

Not classified based on available information.

Components:

toluene:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

Components:

CRISTOBALITE:

Remarks: Lung

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Components:

toluene:

Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 5.5 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l
Exposure time: 48 h



BOSTIK

SAFETY DATA SHEET

Revision Date: 07/12/2022

Print Date: 12/5/2023

SDS Number: 000000156392

Version: 2.1

Isoet™ WD3-A322UV ADHESIVE
™ Trademark, Bostik or its subsidiaries, registered in
various countries
719785

Toxicity to algae : EC50 (Chlorella vulgaris (Fresh water algae)): 134 mg/l
Exposure time: 3 h
Test Type: static test

NOEC (Skeletonema costatum (marine diatom)): 10 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 1.39 mg/l
Exposure time: 40 d
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): 0.74 mg/l
Exposure time: 7 d

PENTA-NA DIETHYLENETRIAMINE PENTAACETATE:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 1,005 - 1,250 mg/l
Exposure time: 96 h
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 245 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 100 mg/l
Exposure time: 28 d
Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 67 mg/l
Exposure time: 18 d
Test Type: static test
Method: OECD Test Guideline 211

PHOSPHORIC ACID, TRIBUTYL ESTER:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 7.66 - 8.74 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 1.58 - 8.43 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae : EC50 (green algae): 2.8 mg/l
Exposure time: 72 h

 BOSTIK		Page: 15
SAFETY DATA SHEET		Revision Date: 07/12/2022
		Print Date: 12/5/2023
		SDS Number: 000000156392
Isoet™ WD3-A322UV ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 719785		Version: 2.1

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.87 mg/l
Exposure time: 21 d

Ecotoxicology Assessment
Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

Persistence and degradability

toluene:

Biodegradability : Result: Readily biodegradable.

PENTA-NA DIETHYLENETRIAMINE PENTAACETATE:

Biodegradability : Result: Not readily biodegradable.

No data available

Bioaccumulative potential

toluene:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 90
Exposure time: 3 d

Partition coefficient: n-octanol/water : log Pow: 2.73 (20 °C)
pH: 7

PHOSPHORIC ACID, TRIBUTYL ESTER:

Bioaccumulation : Species: Medaka, high-eyes (Oryzias latipes)
Bioconcentration factor (BCF): 21 - 35
Exposure time: 38 d
Method: Flow through

Partition coefficient: n-octanol/water : log Pow: 4.00

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : No data available

toluene:

Results of PBT and vPvB assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

 BOSTIK		Page: 16
SAFETY DATA SHEET		Revision Date: 07/12/2022
		Print Date: 12/5/2023
		SDS Number: 000000156392
Isoet™ WD3-A322UV ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 719785		Version: 2.1

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice

- : Do not dispose of waste into sewer.
- Do not contaminate ponds, waterways or ditches with chemical or used container.
- Send to a licensed waste management company.
- Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging

- : Empty remaining contents.
- Dispose of as unused product.
- Empty containers should be taken to an approved waste handling site for recycling or disposal.
- Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

 BOSTIK		Page: 17
SAFETY DATA SHEET		Revision Date: 07/12/2022
		Print Date: 12/5/2023
		SDS Number: 000000156392
Isoet™ WD3-A322UV ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 719785		Version: 2.1

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

Canadian PBT Chemicals	: This product does not contain any components on the DSL that are classified as Persistent, Bioaccumulative and Toxic (PBT) under CEPA.
-------------------------------	--

The components of this product are reported in the following inventories:

TCSI : Not in compliance with the inventory

		Page: 18
SAFETY DATA SHEET		Revision Date: 07/12/2022
		Print Date: 12/5/2023
		SDS Number: 000000156392
Isoset™ WD3-A322UV ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 719785		Version: 2.1

TSCA	: All substances listed as active on the TSCA inventory
AIIC	: Not in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
ENCS	: On the inventory, or in compliance with the inventory
ISHL	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of H-Statements

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.

		Page: 19
SAFETY DATA SHEET		Revision Date: 07/12/2022
		Print Date: 12/5/2023
		SDS Number: 000000156392
Isoset™ WD3-A322UV ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 719785		Version: 2.1

Full text of other abbreviations

AIIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

This sds has been prepared by Bostik. (<http://www.Bostik.com>)

Sources of key data used to compile the Safety Data Sheet : Bostik internal data including own and sponsored test reports
 European Union Law with content from the Official Journal of the European Union.
 European Chemicals Agency; the EU authority implementing the EU's chemicals legislation for companies.
 The German Water Hazard Classes.
 ReachCentrum; a series of support services to help comply with REACH regulations.
 The European Commission; proposing legislation, administering and implementing EU policies, and enforcing EU law.
 The UNECE administers regional agreements implementing

 BOSTIK		Page: 20
SAFETY DATA SHEET		Revision Date: 07/12/2022
		Print Date: 12/5/2023
		SDS Number: 000000156392
Isoet™ WD3-A322UV ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 719785		Version: 2.1

harmonised classification for labelling (GHS) and transport.
 Cefic, the European Chemical Industry Council.
 ESIS European Chemical Substances Information System

Revision Date : 07/12/2022
 Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
 CA / EN